

H38L

Full-function Lobby ATM

The H38L is a full function lobby ATM. This unit can perform cash withdrawals, envelope deposits and check imaging. The H38L supports value-added transactions such as paying bills, dispensing non-cash media (stamps, tickets and coupons) and can be used for advertising products, services and delivering other valuable information.



H38L Full-function Lobby ATM

SPECIFICATIONS

[Industrial PC]

- * Pentium 4 2.8G or higher CPU, 512MB RAM, 80GB HDD, CD-ROM Drive

[Display]

- * 12.1" TFT Color LCD with 2 X4 function display keypads
- * 15" TFT Color LCD with touch screen (optional)
- * Privacy filter with sunlight viewable (optional)
- * Digitized voice guidance

[Keypad]

- * Tactile 4 X 4 numeric metal keypad with English keys of "ENTER", "CLEAR", "CANCEL", local language keys are optional
- * 2X 4 function display keypads
- * PCI EPP
- * Vandal resistant & dust proof
- * Beep responding on key press

[Lead-Through Indicator]

- * Card reader indicator
- * Receipt printer indicator
- * Cash output indicator
- * Envelope deposit indicator

[Operator Interface]

- * Front service panel
- * User-friendly maintenance manager
- * Privilege management with supervisor menu in English
- * Self-diagnosis & error inquiring
- * E-journal output to CD-ROM

[Card Reader/Writer]

- * Motorized card reader/writer (magnetic/smart card, Hi-Co track 1/2/3 read and write, EMV certified.)
- * Card capture capability
- * Anti-fishing/skimming security features
- * Card return on power failure (optional)
- * Contactless smart card reader/writer (optional)
- * DIP card reader/writer (optional)

[Barcode Scanner option]

- * Single-string laser scanning
- * International standard barcode support (CODE39, CODE128, etc.)
- * Maximum scanning distance: 203mm

[Printer]

- * Graphics Receipt Printer
 - 40 column high-speed graphics thermal printer
 - Local character printing
 - Capacity up to 6300 transactions
 - Sideways feature for mini statement printing (optional)
- * Journal Printer
 - 40 column dot matrix or thermal printer
 - Capacity up to 2700 transactions
- * Auto-paging Passbook Printer (optional)
- * Extra Media Printer (optional)
- * A4 Statement Printer (optional)

[Deposit Unit]

- * Motorized envelope feeding
- * Integrated dot matrix printer
- * Envelope capacity: Max. 100 bank notes per envelope
- * Envelope depository bin capacity:
 - Approximate 200 envelopes with 15 notes per envelope
- * Cash/Check Deposit (optional)

[Check Processor (optional)]

- * Check and credit slip processing
- * True MICR read of E13B or CMC7 code line
- * High quality front and rear imaging of documents
- * Rear endorsement printing either single line or multi-line
- * Optional CAR/CAV/LAR
- * Separate enclosures for cash and checks
- * Proof of deposit with check image via ATM receipt

[Dispenser]

- * High-speed dispenser
 - Frictional bundle-cash presenting
 - Dispensing speed: 7 notes per second
 - Maximum 100 notes per bundle
 - Note Cassette: standard 2, maximum 4
 - 1 Reject Vault (integrated): Capacity up to 300 notes
 - Note Cassette capacity: Approximately 3000 new notes
 - Universal media size range support
 - High security: Dual-lock for Note Cassettes and Reject Vault

[Security]

- * Physical:
 - UL291 standard Level 1 safe
 - Dial combination lock plus mechanical lock
- * PCI EPP
- * EMV Level 2 certified
- * DVR surveillance system (optional): Video capture triggered by timing, alarm, transaction or motion detecting
- * Transaction image capture for surveillance (optional)
- * Consumer awareness mirror

[Software]

- * Operating system: Windows XP Pro
- * ATM application software:
 - NDC/NDC+ emulation
 - DDC emulation
 - ISO8583
 - Standard CEN/XFS SP
 - Can be customized to work with any ATM switching system

[Network Communication]

- * Standard TCP/IP, leased line connection
- * PSTN dial-up connection (optional)
- * Wireless connection (optional): GPRS/CDMA
- * SNA/SDLC LU0 (optional) * X.25 (optional)

[Working Environment]

- * Operating temperature:
 - 32°F (0°C) to 122°F (50°C)
- * Relative humidity: 20% to 95% non-condensing

[Power Consumption]

- * AC 220V ± 15%, 50Hz
- * AC 110V ± 15%, 60Hz (optional)
- * Idle: 160W
- * Working: 180W
- * UPS (optional)
 - 1KVA
 - Intelligent emergency power supply and power cut off alarm

[Dimensions & Weight]

- * Height: 62.4 in. (1585mm) * Width: 23.8 in. (605mm)
- * Depth: 33.5 in. (850 mm) * Weight: 1265lbs (575KG)

GRG Banking Equipment Co., Ltd.

163 Pingyun Rd., West Huangpu Ave.,
Guangzhou City, China, 510656

Tel: +86-20-38699033 Fax: +86-20-38699014

E-mail: atm@grgbanking.com

www.GRGBanking.com

Copyright by GRG Banking Equipment Co., Ltd.
All rights reserved.

Regional Representative

In USA, Canada, United Kingdom, Australia, and New Zealand

GRG International

300 Davis Avenue Pass Christian, MS 39571

Tel: 228-452-5000 Fax: 228-452-5005

E-mail: sales@grgatm.com

www.GRGATM.com